

# LHM230P

Specifications						LHM230P
Identification	1.1	Manufacturer				Toyota
	1.2	Manufacturer's type designation				LHM230P
	1.4	Operator type				Hand
	1.5	Load capacity/rated load		Q(t)	kg	2300
	1.6	Load centre distance		c	mm	600
	1.8	Load distance, front axle to fork face		x	mm	945 <sup>1)</sup>
	1.9	Wheelbase		y	mm	1170 <sup>1)</sup>
Weight	2.1	Service weight			kg	75
	2.2	Axle load, with load, drive/castor/fork wheel			kg	375/805
	2.3	Axle load, without load, drive/castor/fork wheel			kg	20/10
Wheels	3.1	Steer/fork wheels: Powerthane (Po), Steel (S), Nylon (N), Polyurethane (P), Rubber (R), Rubber antistatic (Ra)				Po, Ra/Po, S, N, P
	3.2	Wheel size, front			mm	Ø 175x60
	3.3	Wheel size, rear			mm	Ø 85x100/85x75 <sup>2)</sup>
	3.5	Wheels, number front/rear (x = driven wheels)				2/2 or 2/4 <sup>2)</sup>
	3.6	Track width, front		b <sub>10</sub>	mm	148
	3.7	Track width, rear		b <sub>11</sub>	mm	364
	Dimensions	4.4	Lift		h <sub>3</sub>	mm
		Lift height		h <sub>23</sub>	mm	200
4.9		Height of tiller in drive position, min./max.		h <sub>14</sub>	mm	1220
4.15		Height, lowered		h <sub>13</sub>	mm	85
4.19		Overall length		l <sub>1</sub>	mm	1575
4.20		Length to face of forks		l <sub>2</sub>	mm	415
4.21		Overall width		b <sub>1</sub> , b <sub>2</sub>	mm	520/685 <sup>3)</sup>
4.22		Fork dimensions		s/e/l	mm	45/156/1150 <sup>4)</sup>
4.25		Width over forks		b <sub>5</sub>	mm	520/685 <sup>3)</sup>
4.32		Ground clearance, centre of wheelbase		m <sub>2</sub>	mm	40
4.33		Aisle width for pallets 1000x1200 crossways		A <sub>st</sub>	mm	1525 <sup>1)</sup>
4.34		Aisle width for pallets 800x1200 lengthways		A <sub>st</sub>	mm	1725 <sup>1)</sup>
4.35		Turning radius		W <sub>a</sub>	mm	1370 <sup>1)</sup>

1) Distance with forks raised.

2) Single wheel/Bogie wheel.

3) Other widths available on request.

4) Other fork length available: 800/910/1000/1070/1220

Dimensional drawings

